



TablLift™

ECO A HLT2-015-36 Series Scissor Lift Tables



Medium-Duty,
Electrohydraulic
1,500 lb. capacity
For Surface or Pit
Installation

HLT2-015-36-24048

Model Number Format

HLT2 - 015 - 36 - 24048

Series "HLT"
Hydraulic Lift Table

Base Frame Width
2 = 23 1/2"

Capacity
015 = 1,500 lbs.

Vertical Travel
36 = 36 inches

Platform Size
24048 = 24"W x 48"L

Description

ECO A's HLT2-015-36 is an economical, medium-duty electrohydraulic scissor lift with 1,500 lbs. capacity and 36 in. of Vertical Travel.

Standard Features

- HLT2 Lifts have the scissor leg roller entrapped within the base frame and platform for superior stability
- Single-acting cylinders with positive internal stops are fastened at the rod end sleeve with removable axles for enhanced maintainability
- Heavy-duty welded construction designed with a 3-to-1 safety factor, complies with ANSI MH29.1-1994
- PTFE (Teflon®) lined, composite bearings at all wear points. Hardened chrome plated axles used at all bearing surfaces.
- Scissor Legs bolted to base frame and platform at fixed (clevis) end, for enhanced maintainability and ease of disassembly, if required.
- 3/4 HP, 115V/1PH integral power unit. 115VAC control voltage
- Hinged safety maintenance bars.

- Smooth steel tops
- Hard, chrome-plated, polished shafting, hydraulic cylinder piston rods and axles
- 10 ft. power cord (connector not included)
- Contoured Scissor Legs
- Internal high-pressure gear pump with check valve, relief valve, pressure-compensated flow control valve, solenoid valve, suction and return filters
- Includes hydraulic oil

Limited Warranty Policy

Refer to Warranty Form Number WF-0901 for specific details.

Specifications are subject to change without notice.

HLTx Series Lift Tables are one of a group of ECO A Lift Tables and other materials handling products.

HLT2-015-36 Economy Lift Table. Capacity 1,500 lbs.													
Travel	Model	Capacity (pounds)	Edge Load* Maximum		Platform Sizes (Inches)		Base Frame (Inches)	Height (Inches)		Up Speeds (seconds)	Motor Std. HP	Cylinders (Qty.)	Ship* Weight (pounds)
			Static	Rolling	Standard	Maximum		Lowered	Raised				
36"	HLT2-015-36	1,500	1,500	1,000	24 x 48	36 x 60	23 1/2 x 47	7 1/2	43	20	3/4	1	660

*Standard platforms only. Conforms to or exceeds ANSI standard MH29.1-1994.

OPTIONS AVAILABLE:

1.	HLT-PF-0S	Oversized platform up to 36" x 60" (Straight toeguard, smooth tops only)
2.	ELC-P108-01	Foot-operated control, NEMA-1 with guard (Note: Control voltage is 115VAC)
3.	HLT-P009	Accordion Bellows Safety Skirt

Distributed By:

