



# Myti-Lift™ Tables

## ECO A CLMYT Series



Compact,  
Ergonomic,  
Electrohydraulic  
500 to 1,000 lb.  
Capacities  
Stationary or  
Portable

**CLMYT-05-30-12024**

### Model Number Format

**CLMYT- 05- 30**

Series "CLMYT"  
Hydraulic Lift Tables  
Capacity Range  
05 = 500 lbs.  
Travel  
30 = 30"

*Conforms to ANSI Standard MH29.1-1994.*

### Description

ECO A CLMYT-series Lift Tables are electrohydraulic scissor lifts with small platforms and high travel for an infinite number of applications. Load capacities are 500 to 1,000 lbs., travel distances of 30 to 36 in. with minimum platform sizes of 12 x 24 to 16 x 24 in.

### Standard Features

- Minimum platform sizes of 12 x 24 to 16 x 24 in.
- Internally or externally mounted 1/2 HP, 115V, 1PH, 60Hz intermittent duty, 1/2 HP motor is open enclosure.
- 115V operating control voltage
- NEMA-4X constant-pressure (water-tight, oil-tight and corrosion-resistant) "UP-DOWN" pushbutton control station with 8 ft. straight cord
- 10 ft. power cord (plug not included)
- Cylinders with internal stops
- Hard, chrome-plated, polished shafting, hydraulic cylinder piston rods and axles
- Surfaces degreased and finished with two coats of enamel
- Smooth steel tops

- Straight toeguards with yellow and black safety stripes
- Lifetime self-lubricating PTFE lined composite bearings
- Safety restraint maintenance bars
- Internal high-pressure gear pump with check valve, relief valve, pressure-compensated flow control valve, solenoid valve, suction and return filters
- Includes hydraulic oil

### Limited Warranty Policy

Refer to Warranty Form for specific details. Specifications are subject to change without notice. CLMYT Series Lift Tables are one of a group of ECO A Lift Tables and other materials handling products. Call ECO A for additional literature.

**Selector Table for CLMYT Series. Capacities 500 or 1,000 lbs.**

Travel	Model	Capacity (pounds)	Platform Sizes (inches)		Base Frame (Inches)	Height (Inches)***		Up Speed (Seconds)	Motor Std. HP	Cylinders (Qty.)	Ship Weight (pounds)*
			Standard	Maximum		Lowered	Raised				
30"	CLMYT-05-30	500	12 x 24	12 x 24	12 x 24	6	36	20	1/2	2	185
	CLMYT-05-30W	500	16 x 24	24 x 36	16 x 24	6	36	20	1/2	2	208
	CLMYT-10-30	1000	16 x 24	24 x 36	16 x 24	6	36	20	1/2	2	208

\*Standard platforms only. \*\*\*Six (6)" is a nominal dimension, may vary -0" + 1/4"



CLMYT-05-30 and CLMYT-10-30



*Portability Option  
Two Fixed Wheels  
and Two Swivel  
Wheels with Locks*



1/2 HP Power Unit