

Pneumatic Lift Tables

Pneumatic Scissor Lifts

Model Number	Lift Capacity	Vertical Travel	Lowered Height	Raised Height	Base Size W / L	Platform Size W / L	Shipping Weight
AX10 Series							
AX10 - 3648	1000 lbs	21"	8"	29"	36" x 48"	36" x 48"	820 lbs
AX10 - 4848	1000 lbs	21"	8"	29"	36" x 48"	48" x 48"	890 lbs
AX10 - 4856	1000 lbs	21"	8"	29"	36" x 48"	48" x 56"	935 lbs
AX10 - 4860	1000 lbs	21"	8"	29"	36" x 48"	48" x 60"	960 lbs
AX20 Series							
AX20 - 3648	2000 lbs	24"	8"	32"	36" x 48"	36" x 48"	855 lbs
AX20 - 4848	2000 lbs	24"	8"	32"	36" x 48"	48" x 48"	915 lbs
AX20 - 4856	2000 lbs	24"	8"	32"	36" x 48"	48" x 56"	955 lbs
AX20 - 4860	2000 lbs	24"	8"	32"	36" x 48"	48" x 60"	1040 lbs
AX40 Series							
AX40 - 4848	4000 lbs	24"	8"	32"	48" x 48"	48" x 48"	1040 lbs
AX40 - 4856	4000 lbs	24"	8"	32"	48" x 48"	48" x 56"	1115 lbs
AX40 - 4860	4000 lbs	24"	8"	32"	48" x 48"	48" x 60"	1135 lbs



Features

- 1000 - 4000 lb. capacity
- 21" & 24" travel
- 8" lowered height
- 32" raised height
- Air requirements - 80 psi at 15 cfm
- Pressure relief valve standard
- Lifetime warranty on actuator
- Standard pedestal control
- Optional foot control
- AX units designed for stationary use must be lagged to the floor
- Custom platforms available
- Hand control is not available on any Pneumatic lift/tilts

Pneumatic Options

Mechanical Options

Description and Specification
Oversized Platform - platforms can be increased in width and length up to additional 24". Side and end load capacities are derated 2% per inch of increase and oversized models must be lagged to the floor.
Platform with Beveled Edges - welded at 30° angles, increases the standard platform by 4" on all sides.
Pit Mounted Units - for ground level applications require a Platform with Beveled Edges. Lifting Eyes required for installation.
Lifting Eyes - provided for installation and transporting of unit with a sling or lifting chain.
Portable Units - wheeled dolly handle and two 5" fixed wheels (specify side or end mounting) for moving empty lifts. Overall lowered height is not changed when unit is in an operating position. Only available on AXS, AXSR, and AXST. Oversized platform available.
Transportable Units - 6" steel casters, two fixed and two swivel, and a Presto floor lock mounted underneath base frame. Adds 9 3/4" to the lowered height. Only available on AXS, AXSR, and AXST. Oversized platform available.
V Grooved Wheels - 5" steel wheels for Transportable Units only, sold per pair.
Heavy-duty turntables available.

Description and Specification
Detent Stops - manual or spring activated stops for a Turntable, standard stops positioned at 90° increments.
Positioning Lock - Pneumatically actuated lock for turntable tops, securely locks the turntable in any position. Must be used in conjunction with a Turret bearing system.
Conveyor Top - mounted to the lift table platform, these 1.9" diameter rollers on 3" center have a 1000 lb capacity per linear foot. Adds 4" to overall height.
Optional Top Material - for special handling of loads, v tops, aluminum material, stainless steel, diamond plate, etc.
Accordion (Bellows) Skirts - designed to cover the scissor leg assembly of the lift table.
Fork Pockets - used for moving scissor lifts between work stations.
Floor Stands - designed to increase the lowered height of tilters.
Motion Stabilizer - reduces the "bounce" found in pneumatic tilt tables.