

# Heavy Duty Pneumatic Scissor Lifts



| Model Number        | Lift Capacity | Vertical Travel | Lowered Height | Raised Height | Base Size W / L | Platform Size W / L | Shipping Weight |
|---------------------|---------------|-----------------|----------------|---------------|-----------------|---------------------|-----------------|
| <b>AXS20 Series</b> |               |                 |                |               |                 |                     |                 |
| AXS20 - 3648        | 2000 lbs      | 24"             | 12"            | 36"           | 36" x 48"       | 36" x 48"           | 855 lbs         |
| AXS20 - 4848        | 2000 lbs      | 24"             | 12"            | 36"           | 36" x 48"       | 48" x 48"           | 915 lbs         |
| AXS20 - 4856        | 2000 lbs      | 24"             | 12"            | 36"           | 36" x 48"       | 48" x 56"           | 955 lbs         |
| AXS20 - 4860        | 2000 lbs      | 24"             | 12"            | 36"           | 36" x 48"       | 48" x 60"           | 1040 lbs        |
| <b>AXS40 Series</b> |               |                 |                |               |                 |                     |                 |
| AXS40 - 3648        | 4000 lbs      | 24"             | 12"            | 36"           | 36" x 48"       | 36" x 48"           | 1020 lbs        |
| AXS40 - 4848        | 4000 lbs      | 24"             | 12"            | 36"           | 36" x 48"       | 48" x 48"           | 1040 lbs        |
| AXS40 - 4856        | 4000 lbs      | 24"             | 12"            | 36"           | 36" x 48"       | 48" x 56"           | 1115 lbs        |
| AXS40 - 4860        | 4000 lbs      | 24"             | 12"            | 36"           | 36" x 48"       | 48" x 60"           | 1135 lbs        |
| <b>AXS60 Series</b> |               |                 |                |               |                 |                     |                 |
| AXS60 - 4848        | 6000 lbs      | 24"             | 12"            | 36"           | 48" x 48"       | 48" x 48"           | 1170 lbs        |
| AXS60 - 4856        | 6000 lbs      | 24"             | 12"            | 36"           | 48" x 48"       | 48" x 56"           | 1315 lbs        |
| AXS60 - 4860        | 6000 lbs      | 24"             | 12"            | 36"           | 48" x 48"       | 48" x 60"           | 1335 lbs        |
| <b>AXS80 Series</b> |               |                 |                |               |                 |                     |                 |
| AXS80 - 4848        | 8000 lbs      | 24"             | 12"            | 36"           | 48" x 48"       | 48" x 48"           | 1340 lbs        |
| AXS80 - 4856        | 8000 lbs      | 24"             | 12"            | 36"           | 48" x 48"       | 48" x 56"           | 1415 lbs        |
| AXS80 - 4860        | 8000 lbs      | 24"             | 12"            | 36"           | 48" x 48"       | 48" x 60"           | 1435 lbs        |

## Features

- 2000 - 8000 lb. capacity
- 24" travel
- 36" raised heights
- Air requirements 80 psi at 15 cfm
- Lifetime warranty on actuator
- Pressure relief valve standard
- Standard pedestal control
- Optional foot control
- AXS units available in transportable version
- No floor lagging necessary
- Custom platforms available

# Pneumatic Options

## Mechanical Options

| Description and Specification  |
|--|
| Oversized Platform - platforms can be increased in width and length up to additional 24". Side and end load capacities are derated 2% per inch of increase and oversized models must be lagged to the floor.   |
| Platform with Beveled Edges - welded at 30° angles, increases the standard platform by 4" on all sides.  |
| Pit Mounted Units - for ground level applications require a Platform with Beveled Edges. Lifting Eyes required for installation.   |
| Lifting Eyes - provided for installation and transporting of unit with a sling or lifting chain.   |
| Portable Units - wheeled dolly handle and two 5" fixed wheels (specify side or end mounting) for moving empty lifts. Overall lowered height is not changed when unit is in an operating position.<br>Only available on AXS, AXSR, and AXST.<br>Oversized platform available. |
| Transportable Units - 6" steel casters, two fixed and two swivel, and a Presto floor lock mounted underneath base frame. Adds 9 3/4" to the lowered height.<br>Only available on AXS, AXSR, and AXST.<br>Oversized platform available.                                       |
| V Grooved Wheels - 5" steel wheels for Transportable Units only, sold per pair.  |
| Heavy-duty turntables available.   |

| Description and Specification  |
|--|
| Detent Stops - manual or spring activated stops for a Turntable, standard stops positioned at 90° increments.  |
| Positioning Lock - Pneumatically actuated lock for turntable tops, securely locks the turntable in any position. Must be used in conjunction with a Turret bearing system. |
| Conveyor Top - mounted to the lift table platform, these 1.9" diameter rollers on 3" center have a 1000 lb capacity per linear foot. Adds 4" to overall height.            |
| Optional Top Material - for special handling of loads, v tops, aluminum material, stainless steel, diamond plate, etc.   |
| Accordion (Bellows) Skirts - designed to cover the scissor leg assembly of the lift table.   |
| Fork Pockets - used for moving scissor lifts between work stations.  |
| Floor Stands - designed to increase the lowered height of tilters.   |
| Motion Stabilizer - reduces the "bounce" found in pneumatic tilt tables.   |

Distributed by: [www.Lift-Tables.net](http://www.Lift-Tables.net)