

Heavy Duty Pneumatic Scissor Lift & Rotate

Model Number	Lift Capacity	Vertical Travel	Lowered Height	Raised Height	Base Size W / L	Platform Size W / L	Shipping Weight
AXSR20 Series							
AXSR20-3648	2000 lbs	24"	15"	39"	36" x 48"	36" x 48"	1155 lbs
AXSR20-4848	2000 lbs	24"	15"	39"	36" x 48"	48" x 48"	1295 lbs
AXSR20-4856	2000 lbs	24"	15"	39"	36" x 48"	48" x 56"	1385 lbs
AXSR20-4860	2000 lbs	24"	15"	39"	36" x 48"	48" x 60"	1450 lbs
AXSR40 Series							
AXSR40-3648	4000 lbs	24"	15"	39"	36" x 48"	36" x 48"	1370 lbs
AXSR40-4848	4000 lbs	24"	15"	39"	36" x 48"	48" x 48"	1420 lbs
AXSR40-4856	4000 lbs	24"	15"	39"	36" x 48"	48" x 56"	1550 lbs
AXSR40-4860	4000 lbs	24"	15"	39"	36" x 48"	48" x 60"	1595 lbs
AXSR60 Series							
AXSR60-4848	6000 lbs	24"	15"	39"	48" x 48"	48" x 48"	1620 lbs
AXSR60-4856	6000 lbs	24"	15"	39"	48" x 48"	48" x 56"	1750 lbs
AXSR60-4860	6000 lbs	24"	15"	39"	48" x 48"	48" x 60"	1795 lbs
AXSR80 Series							
AXSR80-4848	8000 lbs	24"	15"	39"	48" x 48"	48" x 48"	1720 lbs
AXSR80-4856	8000 lbs	24"	15"	39"	48" x 48"	48" x 56"	1850 lbs
AXSR80-4860	8000 lbs	24"	15"	39"	48" x 48"	48" x 60"	1895 lbs



Features

- 2000 - 8000 lb. capacity
- 24" travel
- Turntable
- Air requirements 80 psi at 15 cfm
- Lifetime warranty on actuator
- Optional Turret bearing
- Pressure relief valve standard
- Standard pedestal control
- Optional foot control
- AXSR units available in transportable version
- No floor lagging necessary
- Oversized turntables available
- Custom design available

Pneumatic Options

Mechanical Options

Description and Specification
Oversized Platform - platforms can be increased in width and length up to additional 24". Side and end load capacities are derated 2% per inch of increase and oversized models must be lagged to the floor.
Platform with Beveled Edges - welded at 30° angles, increases the standard platform by 4" on all sides.
Pit Mounted Units - for ground level applications require a Platform with Beveled Edges. Lifting Eyes required for installation.
Lifting Eyes - provided for installation and transporting of unit with a sling or lifting chain.
Portable Units - wheeled dolly handle and two 5" fixed wheels (specify side or end mounting) for moving empty lifts. Overall lowered height is not changed when unit is in an operating position. Only available on AXS, AXSR, and AXST. Oversized platform available.
Transportable Units - 6" steel casters, two fixed and two swivel, and a Presto floor lock mounted underneath base frame. Adds 9 3/4" to the lowered height. Only available on AXS, AXSR, and AXST. Oversized platform available.
V Grooved Wheels - 5" steel wheels for Transportable Units only, sold per pair.
Heavy-duty turntables available.

Description and Specification
Detent Stops - manual or spring activated stops for a Turntable, standard stops positioned at 90° increments.
Positioning Lock - Pneumatically actuated lock for turntable tops, securely locks the turntable in any position. Must be used in conjunction with a Turret bearing system.
Conveyor Top - mounted to the lift table platform, these 1.9" diameter rollers on 3" center have a 1000 lb capacity per linear foot. Adds 4" to overall height.
Optional Top Material - for special handling of loads, v tops, aluminum material, stainless steel, diamond plate, etc.
Accordion (Bellows) Skirts - designed to cover the scissor leg assembly of the lift table.
Fork Pockets - used for moving scissor lifts between work stations.
Floor Stands - designed to increase the lowered height of tilters.
Motion Stabilizer - reduces the "bounce" found in pneumatic tilt tables.